

# STANDARD COMMUNICATIONS PTY. LTD.

MATERIAL SAFETY DATA SHEET

MT400/401/406G

Drawing 44897-1

## STATEMENT OF HAZARDOUS NATURE

### COMPANY DETAILS:

**Manufacturer's Name:** Standard Communications Pty Ltd

**ABN:** 93 000 346 814

**Address:** 6 Frank Street, Gladesville  
New South Wales, 2111, Australia

**Postal Address:** Locked Bag 2086  
NORTH RYDE NSW 1670

**Phone:** 61 2 9844 6666      **Fax:** 61 2 9844 6600

**Internet:** [www.gme.net.au](http://www.gme.net.au)

**Emergency and Information  
Telephone Number:**

61 2 9844 6666

(Contact during Business Hours  
EST Sydney, Australia)

**Date Issued:** 19 October 2010

**Supersedes:** Rev 0 - 260705



## IDENTIFICATION

<b>Shipping Name:</b>	Lithium Batteries contained in equipment
<b>UN Number:</b>	3091
<b>Product Name/s:</b>	MT400, MT401, MT400G, MT401G, MT401FF, MT401FG, MT406G
<b>Dangerous Goods Class:</b>	Class 9 – Miscellaneous
<b>Other Name/s:</b>	Emergency Position Indicating Radio Beacon (EPIRB)
<b>ERG Code:</b>	9W
<b>Packing Group:</b>	II

### Significant Ingredients of each Cell:

NAME	CAS RN	%
Sulphur Dioxide	7446-09-5	1-25
Acetonitrile	75-05-8	1-6
Carbonblack	1333-86-4	1-5
Lithium	7439-93-2	1-2.5

1. The unit is an Emergency Position Indicating Radio Beacon (EPIRB) and is designed to be provided on watercraft as a safety aid. When activated the EPIRB strobe flashes and radio signals are emitted on internationally recognised VHF and UHF distress channels.
2. Typically in use the EPIRB is deployed in water, where it is designed to float and self right such that the antenna is in a substantially vertical orientation.
3. The integral power source, which cannot normally be accessed without opening the unit, is comprised of two (2) long life LiSO<sub>2</sub> Lithium (high energy density) cells.
4. The battery is not to be removed or tampered with – to be used for purpose only.

### PHYSICAL DESCRIPTION / PROPERTIES

- The enclosure is predominantly constructed of polycarbonate, with a small number of fittings evident on the exterior. When the EPIRB is removed from its mounting bracket the stainless steel tape antenna straightens to be perpendicular to the top face.
- The EPIRB is designed to withstand moderately high levels of shock and vibration consistent with the expected long-term conditions of installation and subsequent deployment.
- In an undamaged state the chassis forms an environmentally sealed enclosure which protects the printed circuit board, electronic components and integral battery.
- Should the chassis be penetrated then the LiSO<sub>2</sub> cells may be exposed to damage:
  - Damaged cells may release highly corrosive and toxic contents; and
  - Disassembly, abuse or destruction of battery or cell may cause violent explosion with scattering of contents.
- Furthermore in respect to the LiSO<sub>2</sub> cells:
  - Heating above 100°C (212 °F) may cause bursting with release of contents; and
  - Heating above 170°C (338 °F) will melt lithium resulting in a severe fire and explosion hazard.
- Cell Composition:
  - Nominally 2.4 grams Lithium per cell.

### HEALTH HAZARD INFORMATION

#### Acute and Chronic Health Effects:

- The cell chemicals are contained in a sealed unit within the EPIRB.
- **Risk of Exposure:** The risk of exposure occurs only if the cell is mechanically or electrically abused. Any contact of electrolyte and extruded lithium with the skin and eyes should be avoided. Inhalation to be avoided.
- **Signs and Symptoms of Exposure:** A shorted Lithium cell can cause thermal and chemical burns upon contact with the skin.
- **Medical Conditions Generally Aggravated by Exposure:** An acute exposure will not generally aggravate any medical condition.

#### Emergency First Aid:

- **Skin Contact:** In case of skin contact with the contents of a cell, flush immediately with water and contact the Poisons Information Centre.
- **Eye Contact:** For eye contact, flush with copious amounts of water for 15 minutes and contact the Poisons Information Centre.
- **Ingestion of Leaked Material:** For advice contact the Poisons Information Centre or a Doctor at once. Urgent hospital treatment is likely to be needed. If swallowed **DO NOT** induce vomiting.
- **Inhalation of Leaked Material:** Remove patient from contaminated area, lay patient down, keep warm and rested. CPR may be required. Transport to Hospital or Doctor without delay.

### PRECAUTIONS FOR USE

- Avoid Mechanical or Electrical Abuse.
- If the cell material is released, remove personnel from the area until the fumes dissipate.
- Provide maximum ventilation to clear out hazardous gases. Cells will not release hazardous gases under normal operation conditions.
- Batteries are capable of long-term storage at temperatures as high as 71<sup>0</sup>C (160<sup>0</sup>F). Storage at lower temperatures will not affect the product. Temperatures above 71<sup>0</sup>C (160<sup>0</sup>F) and storage at elevated temperatures should be avoided.
- **Ventilation:** In the case of cell venting, provide as much ventilation as possible. Avoid confined areas with venting cell.
- Respiratory protection is not necessary under conditions of normal use.
- **Personal Protection:** Is recommended for venting cell by wearing respiratory protection, protective gloves, protective clothing and safety glasses with side shields.

### SAFE HANDLING

**Storage and Transport (Domestic and International):** In compliance with prevailing IATA Dangerous Goods Regulation for Class 9 Goods.

**Waste Disposal Method:** Follow applicable Federal, State and Local regulations for disposal/recycling of products with Lithium Batteries.

- Lithium batteries and cells are best disposed of as a non-hazardous waste when discharged.
- If waste lithium cells are still fully charged or only partially discharged, then can be considered a reactive hazardous waste because of significant amounts of un-reacted lithium in the battery. The cells must be neutralised through an approved secondary treatment facility prior to disposal as a hazardous waste.

**Disclaimer:** The information included herein is believed to be accurate and represents the best information available to us. However, we make no warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine suitability of this information for their particular use.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from STANDARD COMMUNICATIONS PTY. LTD.